



TDM-150 LCD Timer Displays

Overview

The TDM-150 LCD Timer Displays show the VoteLynx presentation timer count in minutes & seconds to presenters and audience in the meeting room. Large red, yellow, and green graphics indicate start, stop and wrap-up cues. Large bright green numbers give presenters a visual status of how much time they have left to speak during the meeting.

TDM-150 Timer Displays are available in two styles, both with 2.6" diagonal LCD displays. The TDM-150F is designed for podium or in-desk mounting and fits into most single gang electrical openings. The TDM-150D is a desktop version for use in tabletop applications. Both models contain a configurable audio annunciator to provide audio cues and prompts as desired.

The timer display modules may be used with any VoteLynx system configuration. One or more timer displays of either configuration may be connected together. For example, one timer display could be located on the podium top surface for a presenter to see while another display could be located on the rear of the podium for city council members to see. Optional driver module VL-VP-OPT5 is available to control microphone LED light rings.



TDM-150F Flush Mount



TDM-150D Desktop

Features

- Vivid 2.6" TFT active matrix color LCD with white LED backlighting
- Large bright green numbers show timer count
- Brilliant green, yellow and red graphic cue indicators
- Simple Ethernet IP interface connects timer displays to VoteLynx systems
- Desktop or single gang wall box mountable
- Configurable audio annunciator
- Three configurable general purpose I/O pins
- 16 bit color graphics
- Optional driver module for microphone LED ring

Specifications

Display	2.6" Diagonal TFT LCD
Screen Resolution	400 x 240 pixels
Brightness	180 nits, LED backlight
LCD Colors	65,536 colors (16 bit)
Network	TDM-150F: 10/100 Base-T Ethernet on RJ-45 connector TDM-150D: Attached 10 foot 10/100 Base-T Ethernet cable
Audio	Variable frequency piezoelectric speaker
Mounting	TDM-150F: Single gang wall plate TDM-150D: Desktop
Dimensions (mm)	TDM-150F: 114.5 W x 70 H x 35 D TDM-150D: 102 W x 71 H x 106 D
Weight	TDM-150F: 0.12 Kg TDM-150D: 0.23 Kg
Operating Temperature	0°C to 50°C
Storage Temperature	-10°C to 60°C
Supply Voltage	IEEE-802.3af POE or 5 Volts DC
Power Consumption	1.78 W
Power Connection	TDM-150F: 2-pin removable Phoenix style 3.81 mm terminal plug TDM-150D: Attached 10 foot cable with 2.1 mm DC coaxial power jack for 5 volt operation