



TDM-170 LCD Timer Display

Overview

The TDM-170 LCD Timer Displays show the VoteLynx presentation timer count in minutes & seconds to presenters and audience in the meeting room. Large red, yellow, and green graphics indicate start, stop and wrap-up cues. Large bright green numbers give presenters a visual status of how much time they have left to speak during the meeting.

TDM-170 Timer Displays features a 4.3" diagonal LCD display. It is designed for wall mounting. The TDM-170 contains a configurable audio annunciator to provide audio cues and prompts as desired.

The timer display modules may be used with any VoteLynx system configuration. One or more timer displays of either configuration may be connected together. For example, one timer display could be located on the podium top surface for a presenter to see while another display could be located on the rear of the podium for city council members to see.



Features

- Vivid 4.3" TFT active matrix color LCD with white LED backlighting
- Large bright green numbers show timer count
- Brilliant green, yellow and red graphic cue indicators
- Simple Ethernet IP interface connects timer displays to VoteLynx systems
- Desktop or wall mountable
- Configurable audio annunciator
- Two configurable general purpose I/O pins
- 16 bit color graphics

Specifications

Display	4.3" Diagonal TFT LCD
Screen Resolution	480 x 270 pixels
Brightness	400 nits, LED backlight
LCD Colors	65,536 colors (16 bit)
Network	Attached one foot 10/100 Base-T Ethernet cable. Optional lengths available.
Audio	Variable frequency piezoelectric speaker
Mounting	Easy single hole wall mount tab
Dimensions	7.87"W x 3.94"H x 1.57"D 197.61mm W x 100.0mm H x 39.88mm D
Weight	15 oz, 0.43 Kg
Operating Temperature	0°C to 50° C
Storage Temperature	-10° C to 60° C
Supply Voltage	IEEE-802.3af POE or 5 Volts DC
Power Consumption	1.78 W
Power Connection	Attached one foot cable with 2.1 mm DC coaxial power jack for 5 volt operation. Optional lengths available.